

## “Normal” Mini Clip



W1

The use of malleable mild steel in the manufacture of the “Normal” mini clip means that when tightened, the clip adapts perfectly to the hose, clamping firmly but gently.


This clip is recommended for use with gaseous fluids at low pressure and on small-bore or thin-walled hoses.

“Normal” also has many applications in the automotive industry.

*\* The maximum pressure may vary depending on the type of hose and coupling used.*

Application Ø											
mm	Part nº	r	e	a	b	s	Maximum values		Box Quantity (MOQ)	Outer Packing	
							Torque (Nm)	Pressure (Bars)			
6	0301051-0	M3	5	8,4	9	0,5	0,4	15	100	1.600	
8	0301052-8	M3	5	9	9	0,5	0,4	14	100	1.600	
9	0301053-6	M4	6	10	10	0,5	1	15	100	1.600	
9,5-10	0301054-4	M4	6	10	10	0,5	1	14	100	1.600	
10-11	0301055-2	M4	6	10	10	0,5	1	13	100	1.600	
12-13	0301056-0	M4	6	10	10	0,5	1	12	100	1.600	
13-14	0301057-9	M4	6	10	10	0,5	1	12	100	1.600	
14-15	0301058-7	M4	6	10	10	0,5	1	12	100	1.600	
15-17	0301059-5	M4	6	10	10	0,5	1	12	100	1.600	
16-18	0301060-8	M4	6	10	10	0,5	1	11	100	1.600	
18-20	0301061-6	M4	6	10	10	0,5	1	10	100	1.600	
19-21	0301062-4	M4	6	10	10	0,5	1	10	100	800	
20-22	0301063-2	M4	6	10	10	0,5	1	10	100	800	
22-25	0301064-0	M4	6	10	10	0,5	1	9	100	800	
23-26	0301065-9	M4	6	10	10	0,5	1	9	100	800	
25-28	0301066-7	M4	6	10	10	0,5	1	8	100	800	
26-29	0301067-5	M4	6	10	10	0,5	1	8	100	800	
29-32	0301068-3	M4	6	10	10	0,5	1	8	100	800	

\* It is recommended to apply 75% of the maximum values contained in the table.

TECHNICAL INFORMATION	
	<b>MATERIAL</b> BAND: STEEL ST3 K32 (EN10215) SCREW: STEEL GRADE 6 NUT: STEEL GRADE 6
	<b>FINISH</b> GREY-WHITE Cr3 ZINC-PLATED
	<b>CORROSION RESISTANCE</b> 72 HOURS SALT SPRAY (ASTM B-117)

