



W1

ASFA L (9 mm) Hose Clamp Galvanized Steel - W1

Thanks to the exclusive design of the housing and the high-strength screw, the ASFA LW1 Worm-Drive Clip has excellent performance while being at the same time very compact.

The cold-formed stamped 9mm band, smoothed on the underside, combined with the beveled band edges protects the hose from any damage.

DIN 3017. The ASFA LW1 hose clip complies fully with the DIN 3017 norm and also with the directive EU 2002/95/EC. This clip is ideal for general industrial applications.

** The maximum application pressure can vary depending on the type of hose used and the geometry of the coupling.*

Application Ø											
mm	Part nº	L max.	S +0,10	h max.	a +0,3 a -0,2	b max.	Maximum values		Box Quantity (M00)	Outer Packing	
							Torque (Nm)	Pressure (Bars)			
8-12	0300874-5	17,5	0,65	9,2	7	11,5	1,5	15	200	1600	
8-16	0300875-3	22,1	0,65	10,5	9	14	3	40	200	800	
12-22	0300876-1	22,1	0,65	10,5	9	14	3	40	200	800	
16-27	0300877-0	23,6	0,75	10,5	9	14	3,5	38	200	800	
20-32	0300878-8	23,6	0,75	10,5	9	14	3,5	36	200	800	
25-40	0300879-6	25,6	0,75	10,5	9	14	4	32	100	400	
30-45	0300880-9	25,6	0,75	10,5	9	14	4	28	100	800	
32-50	0300881-7	25,6	0,75	10,5	9	14	4	24	100	800	
40-60	0300882-5	25,6	0,75	10,5	9	14	4	19	100	400	
50-70	0300883-3	29,6	0,75	10,5	9	14	4	17	100	100	
60-80	0300884-1	29,6	0,75	10,5	9	14	4	15	100	100	
70-90	0300885-0	29,6	0,75	10,5	9	14	4	13	50	400	
80-100	0300886-8	29,6	0,75	10,5	9	14	4	11	50	400	
90-110	0300887-6	29,6	0,75	10,5	9	14	4	10	25	200	
100-120	0300888-4	29,6	0,75	10,5	9	14	4	9	25	200	
110-130	0300889-2	29,6	0,75	10,5	9	14	4	8	25	200	
120-140	0300890-5	29,6	0,75	10,5	9	14	4	7	25	200	
130-150	0300891-3	29,6	0,75	10,5	9	14	4	6	25	200	
140-160	0300892-1	29,6	0,75	10,5	9	14	4	5	25	25	

** It is recommended to apply 75% of the maximum values contained in the table.*

TECHNICAL INFORMATION	
MATERIAL	BAND AND HOUSING: GALVANIZED STEEL (EN 1.0935) SCREW: STEEL Qst 36-3 (DIN 1.0214)
FINISH	BAND AND HOUSING: GALVANIZED STEEL SCREW: GREY-WHITE Cr3 ZINC-PLATED
CORROSION RESISTANCE	144 HOURS SALT SPRAY (ASTM B-117)
MAXIMUM TIGHTENING SPEED (RPM)	540 ±5

