

ASFA S (12 mm) Hose Clamp AISI 430 Stainless Steel -W3 – Black



W3

This clamp is manufactured in AISI 430 with an additional matt-black surface treatment which increases its corrosion resistance.

Thanks to the surface treatment this clamp can be mounted discreetly in any application, making it a favourite in automotive or motorcycle applications.

The geometry, band, stamping, housing and screw are identical to other ASFA clamps, meaning that the performance is not altered in any way.

DIN 3017. The Black ASFA SW3 hose clip complies fully with the DIN 3017 norm and also with the directive EU 2002/95/EC.

** The maximum application pressure can vary depending on the type of hose used and the geometry of the coupling.*

Application Ø										
mm	Part nº	L max.	S +0,10	h max.	a +0,3 a -0,1	b max.	Maximum values		Box Quantity (MOQ)	Outer Packing
							Torque (Nm)	Pressure(Bars)		
16-27	7301620-6	29,6	0,85	11	12,2	16,7	4,5	40	50	400
20-32	7301621-4	29,6	0,85	11	12,2	16,7	5,5	40	50	400
25-40	7301622-2	29,6	0,85	11	12,2	16,7	5,5	40	50	400
30-45	7301623-0	29,6	0,85	11	12,2	16,7	5,5	35	50	400
32-50	7301624-9	29,6	0,85	11	12,2	16,7	6,5	35	50	200
40-60	7301625-7	29,6	0,85	11	12,2	16,7	6,5	30	50	400
50-70	7301626-5	29,6	0,85	11	12,2	16,7	7	25	50	400
60-80	7301627-3	29,6	0,85	11	12,2	16,7	7	20	50	50
70-90	7301628-1	29,6	0,85	11	12,2	16,7	7	17	50	50
80-100	7301629-0	29,6	0,85	11	12,2	16,7	7	14	25	200
90-110	7301630-2	29,6	0,85	11	12,2	16,7	7	12	25	200
100-120	7301631-0	29,6	0,85	11	12,2	16,7	7	10	25	200
110-130	7301632-9	29,6	0,85	11	12,2	16,7	7	8	25	25
120-140	7301633-7	29,6	0,85	11	12,2	16,7	7	7	25	25
130-150	7301634-5	31,6	0,85	11	12,2	16,7	7	6	25	25
140-160	7301635-3	31,6	0,85	11	12,2	16,7	7	5	25	25
150-170	7301636-1	31,6	0,85	11	12,2	16,7	7	4	25	25
160-180	7301637-9	31,6	0,85	11	12,2	16,7	7	3	25	25
170-190	7301638-7	31,6	0,85	11	12,2	16,7	7	2	10	10
180-200	7301639-6	31,6	0,85	11	12,2	16,7	7	2	10	10

** It is recommended to apply 75% of the maximum values contained in the table.*

TECHNICAL INFORMATION	
MATERIAL	BAND AND HOUSING: STAINLESS STEEL X6Cr17(AISI-430) SCREW: STAINLESS STEEL (AISI-430)
FINISH	DELTA SEAL BLACK
CORROSION RESISTANCE	250 HOURS SALT SPRAY (ASTM B-117)
MAXIMUM TIGHTENING SPEED (RPM)	540 ±5

