




Bridge Clamp ASFA S (12 mm)

ASFA S Bridge Clamps with 12mm bandwidth and manufactured with one or two bridges are an ideal solution for hoses with an outer helix. The geometry and design of the bridges ensure a leaktight fit. These clamps are specially recommended for use on medium-sized and large bore hose mainly used for ventilation or extraction.

** The maximum application pressure can vary depending on the type of hose used and the geometry of the coupling.*

Application Ø mm	Material qualities	Number of bridges	Bridge Position	S +0,10	h max.	a +0,3 a-0,2	b max.	Maximum values		Box Quantity (MOQ)
								Torque (Nm)	Pressure (Bars)	
32-50	W1 W2 W3 W4 W5	1-2	right/left	0,85	11	12	16,7	6,5	32	50
40-60	W1 W2 W3 W4 W5	1-2	right/left	0,85	11	12	16,7	6,5	28	50
50-70	W1 W2 W3 W4 W5	1-2	right/left	0,85	11	12	16,7	7	23	50
60-80	W1 W2 W3 W4 W5	1-2	right/left	0,85	11	12	16,7	7	18	50
70-90	W1 W2 W3 W4 W5	1-2	right/left	0,85	11	12	16,7	7	15	50
80-100	W1 W2 W3 W4 W5	1-2	right/left	0,85	11	12	16,7	7	12	25
90-110	W1 W2 W3 W4 W5	1-2	right/left	0,85	11	12	16,7	7	10	25
100-120	W1 W2 W3 W4 W5	1-2	right/left	0,85	11	12	16,7	7	9	25
110-130	W1 W2 W3 W4 W5	1-2	right/left	0,85	11	12	16,7	7	8	25
120-140	W1 W2 W3 W4 W5	1-2	right/left	0,85	11	12	16,7	7	7	25
130-150	W1 W2 W3 W4 W5	1-2	right/left	0,85	11	12	16,7	7	6	25
140-160	W1 W2 W3 W4 W5	1-2	right/left	0,85	11	12	16,7	7	5	25
150-170	W1 W2 W3 W4 W5	1-2	right/left	0,85	11	12	16,7	7	4	25
160-180	W1 W2 W3 W4 W5	1-2	right/left	0,85	11	12	16,7	7	3	25
170-190	W1 W2 W3 W4 W5	1-2	right/left	0,85	11	12	16,7	7	2	10
180-200	W1 W2 W3 W4 W5	1-2	right/left	0,85	11	12	16,7	7	2	10
190-210	W1 W2 W3 W4 W5	1-2	right/left	0,85	11	12	16,7	7	1,8	10
200-220	W1 W2 W3 W4 W5	1-2	right/left	0,85	11	12	16,7	7	1,8	10
210-230	W1 W2 W3 W4 W5	1-2	right/left	0,85	11	12	16,7	7	1,6	10
220-240	W1 W2 W3 W4 W5	1-2	right/left	0,85	11	12	16,7	7	1,6	10

** It is recommended to apply 75% of the maximum values contained in the table.*

	TECHNICAL INFORMATION	
	MATERIAL	W1: GALVANIZED STEEL W2,W3,W4,W5: STAINLESS STEEL AISI-430, AISI-304, AISI-316
	FINISH	W1: GALVANIZED STEEL W2, W3, W4, W5: STAINLESS STEEL
	CORROSION RESISTANCE	ACCORDING TO MATERIAL USED
	MAXIMUM TIGHTENING SPEED (RPM)	540 ±5

