



Fixed diameter "S" Clamp

The fixed diameter "S" clamp was designed to ensure the best possible fit of hose and coupling. The clamping range of this clamp is minimal, meaning that the diameter of the clamp before and after tightening is very similar. Once the clamp has been mounted and tightened it fits the desired diameter exactly. Another advantage is that very little tightening is required to reach the required torque. The design of the "S" clamp means that it can be used to assemble hoses with metal or plastic couplings. It is particularly recommended for certain sectors ranging from medical machinery manufacture to cars and motorcycles.

DIN3017-2

** This clamp can be supplied in diameters up to 120mm and in bandwidths up to 20mm.*

W1

Application Ø											
d	Article	Part n°	a	L max.	d2	b2	s1 +0,2-0,1	h	s2	Box Quantity (MOQ)	Outer Packing
10	ADF10/9	0303201-0	9	31	M.4	10,5	0,4	11	Iso 1207	500	2.000
11	ADF11/9	0303202-9	9	31	M.4	10,5	0,4	11	Iso 1207	500	500
12	ADF12/9	0303203-7	9	31	M.4	10,5	0,4	11	Iso 1207	500	2.000
13	ADF13/9	0303204-5	9	31	M.4	10,5	0,4	11	Iso 1207	500	500
14	ADF14/9	0303205-3	9	31	M.4	10,5	0,4	11	Iso 1207	500	500
15	ADF15/9	0303206-1	9	31	M.4	10,5	0,4	11	Iso 1207	500	2.000
16	ADF16/9	0303207-0	9	31	M.4	10,5	0,4	11	Iso 1207	500	1.000
17	ADF17/9	0303208-8	9	31	M.4	10,5	0,4	11	Iso 1207	500	500
18	ADF18/9	0303209-6	9	31	M.4	10,5	0,4	11	Iso 1207	250	1.000
19	ADF19/9	0303210-9	9	31	M.4	10,5	0,4	11	Iso 1207	250	1.000
20	ADF20/9	0303211-7	9	31	M.4	10,5	0,4	11	Iso 1207	250	1.000
21	ADF21/12	0303274-0	12	35	M.5	14	0,5	13,5	Din 931 (8)	250	1.000
22	ADF22/12	0303275-8	12	35	M.5	14	0,5	13,5	Din 931 (8)	200	800
23	ADF23/12	0303276-6	12	35	M.5	14	0,5	13,5	Din 931 (8)	250	250
24	ADF24/12	0303277-4	12	35	M.5	14	0,5	13,5	Din 931 (8)	200	800
25	ADF25/12	0303278-2	12	35	M.5	14	0,5	13,5	Din 931 (8)	200	800
26	ADF26/12	0303279-0	12	35	M.5	14	0,5	13,5	Din 931 (8)	200	800
27	ADF27/12	0303280-3	12	35	M.5	14	0,5	13,5	Din 931 (8)	200	200
28	ADF28/12	0303281-1	12	35	M.5	14	0,5	13,5	Din 931 (8)	250	250
29	ADF29/12	0303282-0	12	35	M.5	14	0,5	13,5	Din 931 (8)	100	400
30	ADF30/12	0303283-8	12	35	M.5	14	0,5	13,5	Din 931 (8)	100	400
21	ADF 21/15	0303334-7	15	40	M.6	17	0,6	17	Din 931 - (10)	250	250
23	ADF 23/15	0303336-3	15	40	M.6	17	0,6	17	Din 931 - (10)	250	250
25	ADF 25/15	0303338-0	15	40	M.6	17	0,6	17	Din 931 - (10)	250	250
26	ADF 26/15	0303339-8	15	40	M.6	17	0,6	17	Din 931 - (10)	250	250
31	ADF31/15	0303344-3	15	40	M.6	17	0,6	17	Din 931 - (10)	100	400
32	ADF32/15	0303345-1	15	40	M.6	17	0,6	17	Din 931 - (10)	100	400
33	ADF33/15	0303346-0	15	40	M.6	17	0,6	17	Din 931 - (10)	100	400
34	ADF34/15	0303347-8	15	40	M.6	17	0,6	17	Din 931 - (10)	100	400
35	ADF35/15	0303348-6	15	40	M.6	17	0,6	17	Din 931 - (10)	100	400
36	ADF36/15	0303349-4	15	40	M.6	17	0,6	17	Din 931 - (10)	100	100
44	ADF 44/15	0303357-4	15	40	M.6	17	0,6	17	Din 931 - (10)	100	100
46	ADF 46/15	0303359-0	15	40	M.6	17	0,6	17	Din 931 - (10)	100	100

TECHNICAL INFORMATION	
MATERIAL	BAND: STEEL DIN 1.0935 SCREW: 8.8 GRADE STEEL SILVER-WHITE Cr3 ZINC-PLATED NUT: 6 GRADE STEEL SILVER-WHITE Cr3 ZINC-PLATED
FINISH	GALVANIZED STEEL
CORROSION RESISTANCE	72 HOURS SALT SPRAY (ASTM B-117)

